

BAY OIL COPMANY
38 PAINFIELD STREET
CHICOPEE, MA 01013
413-737-7728

AQUA-SAFE Concrete Sealer
Waterproofing Concrete Sealer

Description

AQUA-SAFE is ready to use, solvent free, semi-mastic, water base water proofing sealer for all concrete above and below ground surfaces.

Benefits

- VOC Compliant
- Easy Clean up with water
- Non Flammable – no fire risk
- Dries Quickly
- Bonds on damp or green concrete

Surface Preparation

All surfaces must be free of oil, Grease, rust scale, loose paint and dirt

Application

AQUA-SAFE should be mixed well. Apply with roller, brush or suitable Sprayer. Coating will depend on Condition or porosity of surfaces. Approximately 1 gal/50 sq. ft. Temperature above 50 degrees Fahrenheit.

Clean up

Fresh coating can be removed with water Kerosene or mineral spirits if coating has Started to dry. Keep application in water.

Physical Properties

Weight per gallon 8.4-8.9 lb.
Typical solids 45% wt.
Non Flammable – wet
Solids approximately 45% Wet
Drying Time Touch – 4 hours

Regulatory Data

Volatile Organic Compound
(VOC) = 0 gr./liter
HMIS rating H2, F-1, R-1, PP-X
RCRA Hazardous Substance – none
Sara Title III listing – RQ Value 100 lb.

Compliance

ASTM D 1187 Type I
ASTM D 1227 Type III class 1

Shipping

5 gallon can
55 gallon drum
Bulk container

Caution

Keep from freezing
Note: See MSDS for further environmental information

Coverage

Approximately 4 gals./100 sq. ft.
Film Thickness Wet 64 mils, Dry 32 mils
Note: Dry Thickness = ½ Wet Thickness